

Adapter cable set

111.7028

- ▶ For current clamps and sensors with 4mm plugs (connection to the AUX-Port of PQ-Box 200/300)



1. Use

This device is used for the connection of current clamps and sensors to the AUX-Port of PQ-Box 200/300 with 4mm banana plugs.

The free adapter cable set enables to use additional current clamps or sensors for the PQ-Box. The input current range lies at 1000 mV AC resp. 1400 mV DC.

Caution:

For usage of current clamps/sensors with voltage output only. Current clamps with current output may cause destruction of the PQ-Box.

2. Structure

The flexible and shielded measurement cable consists of a cable with 7-pole Amphenol plug on one end and 2 x 4 mm banana plugs on the other end.

3. Dimensions and weight

Length in mm	2000		
Weight in g	100		

4. Technical Data

Voltage:	Max. 30V
Cross-section:	2x0,5mm ²
Plug:	Amphenol
Voltage class:	Low-voltage

We take care of it.

5. Ordering Information

FEATURE	ORDER CODE
Adapter cable set ● Adapter cable, 2-pole, Length 2m	111.7028

A. Eberle GmbH & Co. KG

Frankenstraße 160
D-90461 Nürnberg

Tel.: +49 (0) 911 / 62 81 08-0
Fax: +49 (0) 911 / 62 81 08 96
E-Mail: info@a-eberle.de

<http://www.a-eberle.de>

Version: 9/28/2018 8:20 AM

Copyright 2013 by A. Eberle GmbH & Co. KG
Subject to change without notice.